



## P-LIGHT 27

wall and ceiling light, emergency exit light, LED, 6000K, white, L/W/H 26.5/4.5/21 cm, 3,5W

Article number	240000
Lamp	SMD LED
Product family	P-Light
Feed-in capability	No
Lamp included	No
Width	26.5 cm
Height	21 cm
Depth	4.5 cm
Net weight	0.74 kg
Gross weight	0.93 kg
Voltage	220-240 ~50 Volts
Protection class	II
Material	ABS/plastic PC
Colour	white
Way of mounting	Surface wall / Surface ceiling mounting
Average lifespan	25000 Hours
Colour temperature	6000 Kelvin
Colour rendering index	70
Luminous flux	32 lm
Energy efficiency class	A++
fastCalcEnabled	No
ranking	500
Catalogue page	BIG WHITE 2017: 721

The P-LIGHT 27 emergency lighting system is suitable for use as a wall and ceiling light. The safety lights are fitted with a built-in Ni-MH battery with an automatic self-test. The detection range is 24 m. The emergency operating time of the luminaires is three hours. The luminaires can be operated permanently switched on / stand-by operation. The luminaire is connected directly to the 230V mains supply. Other variants of the P-LIGHT series are available. The luminaire is supplied with three signs with different arrow directions (right / left / down). As an option, other signs are available.