



LED insert for GLASS PLOT and LED PLOT round

2,6W, blue, IP67

Type of lamp Lamp Lamp LED Number of light sources Lamp included Yes Height 1.4 cm Diameter 6.2 cm Net weight 0.152 kg Gross weight Voltage 12 Volt Max. wattage 2.6 Watt Protection class III Material plastic Way of mounting Surface wall mounting / surface floor mounting / surface ceiling mounting Remark 1 Operate only with a conventional transformer Remark 2 150 cm connection lead incorporated Average lifespan Luminous flux Suitable for lamps from EEC Suitable for lamps up to EEC Average lifespan A A++	Article number	550217
Number of light sources Lamp included Yes Height 1.4 cm Diameter 6.2 cm Net weight 0.152 kg Gross weight 0.179 kg Voltage 12 Volt Max. wattage 2.6 Watt Protection class III Material plastic Way of mounting surface wall mounting / surface floor mounting / surface ceiling mounting Remark 1 Operate only with a conventional transformer Remark 2 150 cm connection lead incorporated Average lifespan 20000 Hours Luminous flux 65 lm Suitable for lamps from EEC Suitable for lamps A++	Type of lamp	LED lamp
Sources Lamp included Yes Height 1.4 cm Diameter 6.2 cm Net weight 0.152 kg Gross weight Voltage 12 Volt Max. wattage 2.6 Watt Protection class III Material plastic Way of mounting surface wall mounting / surface floor mounting / surface ceiling mounting Remark 1 Operate only with a conventional transformer Remark 2 Average lifespan Luminous flux Suitable for lamps from EEC Suitable for lamps A++	Lamp	LED
Height 1.4 cm Diameter 6.2 cm Net weight 0.152 kg Gross weight 0.179 kg Voltage 12 Volt Max. wattage 2.6 Watt Protection class III Material plastic Way of mounting surface wall mounting / surface floor mounting / surface ceiling mounting Remark 1 Operate only with a conventional transformer Remark 2 150 cm connection lead incorporated Average lifespan 20000 Hours Luminous flux 65 lm Suitable for lamps from EEC Suitable for lamps		8
Diameter 6.2 cm Net weight 0.152 kg Gross weight 0.179 kg Voltage 12 Volt Max. wattage 2.6 Watt Protection class III Material plastic Way of mounting surface wall mounting / surface floor mounting / surface ceiling mounting Remark 1 Operate only with a conventional transformer Remark 2 150 cm connection lead incorporated Average lifespan 20000 Hours Luminous flux 65 lm Suitable for lamps from EEC Suitable for lamps	Lamp included	Yes
Net weight O.152 kg Gross weight O.179 kg Voltage 12 Volt Max. wattage 2.6 Watt Protection class III Material plastic Way of mounting surface wall mounting / surface floor mounting / surface ceiling mounting Remark 1 Operate only with a conventional transformer Remark 2 150 cm connection lead incorporated Average lifespan 20000 Hours Luminous flux 65 lm Suitable for lamps from EEC Suitable for lamps A++	Height	1.4 cm
Gross weight Voltage 12 Volt Max. wattage 2.6 Watt Protection class III Material plastic Way of mounting surface wall mounting / surface floor mounting / surface ceiling mounting Remark 1 Operate only with a conventional transformer Remark 2 150 cm connection lead incorporated Average lifespan 20000 Hours Luminous flux 65 lm Suitable for lamps from EEC Suitable for lamps A++	Diameter	6.2 cm
Voltage 12 Volt Max. wattage 2.6 Watt Protection class III Material plastic Way of mounting surface wall mounting / surface floor mounting / surface ceiling mounting Remark 1 Operate only with a conventional transformer Remark 2 150 cm connection lead incorporated Average lifespan 20000 Hours Luminous flux 65 lm Suitable for lamps from EEC Suitable for lamps	Net weight	0.152 kg
Max. wattage Protection class III Material plastic Way of mounting Surface wall mounting / surface floor mounting / surface ceiling mounting Remark 1 Operate only with a conventional transformer Remark 2 150 cm connection lead incorporated Average lifespan 20000 Hours Luminous flux 65 lm Suitable for lamps from EEC Suitable for lamps A++	Gross weight	0.179 kg
Protection class III Material plastic Way of mounting surface wall mounting / surface floor mounting / surface ceiling mounting Remark 1 Operate only with a conventional transformer Remark 2 150 cm connection lead incorporated Average lifespan 20000 Hours Luminous flux 65 lm Suitable for lamps from EEC Suitable for lamps	Voltage	12 Volt
Material plastic Way of mounting surface wall mounting / surface floor mounting / surface ceiling mounting Remark 1 Operate only with a conventional transformer Remark 2 150 cm connection lead incorporated Average lifespan 20000 Hours Luminous flux 65 lm Suitable for lamps from EEC Suitable for lamps	Max. wattage	2.6 Watt
Way of mounting Surface wall mounting / surface floor mounting / surface ceiling mounting Remark 1 Operate only with a conventional transformer Remark 2 150 cm connection lead incorporated Average lifespan 20000 Hours Luminous flux 65 lm Suitable for lamps from EEC Suitable for lamps A++	Protection class	III
Suitable for lamps Remark 1 Operate only with a conventional transformer 150 cm connection lead incorporated Average lifespan 20000 Hours Luminous flux Suitable for lamps from EEC Suitable for lamps A A++	Material	plastic
Remark 2 Average lifespan Luminous flux Suitable for lamps from EEC Suitable for lamps A A A A A A A A A A A A A	Way of mounting	
Average lifespan 20000 Hours Luminous flux 65 lm Suitable for lamps from EEC Suitable for lamps A	Remark 1	Operate only with a conventional transformer
Luminous flux Suitable for lamps from EEC Suitable for lamps A A	Remark 2	150 cm connection lead incorporated
Suitable for lamps from EEC Suitable for lamps A	Average lifespan	20000 Hours
from EEC Suitable for lamps A A	Luminous flux	65 lm
· A++		A
		A++

Low-voltage LED insert for the combined usage with one of the BIG LED PLOT ROUND covers. The electrical connection is made via a separately available and toroidal 12V transformer. This insert is available in various colours and rated IP67 it is suitable for outdoor use. This luminaire contains built-in LED lamps. EEK: A - A++. The lamps cannot be changed in the luminaire.