






# HIDE

CEILING RECESSED



## 1.0 LED111

LED 10W | 220-240VAC | 50-60Hz  
AC-COB 3-step | phase-cut dim  
aluminium powder coated

0.93kg IP20 3-0.3-1 38°

45°/45° 45°/45° 215 4-25

	CODE
	117268W
	117268S
	117268B

### Light Colour Selection

	LUMEN   CRI	CODE
2700K	710   >80	2
3000K	730   >80	4

## 1.0 LED111 HO

LED 15W | 220-240VAC | 50-60Hz  
AC-COB 3-step | phase-cut dim  
aluminium powder coated

0.93kg IP20 3-0.3-1 30°

45°/45° 45°/45° 215 4-25

	CODE
	117278W
	117278S
	117278B

### Light Colour Selection

	LUMEN   CRI	CODE
2700K	1050   >80	2
3000K	1200   >80	4

## 1.0 QR111

QR111 max.75W | G53  
12V | excl. power supply  
aluminium powder coated

0.73kg IP20 3-0.9-1

45°/45° 45°/45° 215 4-25

	CODE
	117230W0
	117230S0
	117230B0

### ALWAYS USE

	CODE
12V   10W dim	90221401
12V   25W dim	90221701
12V   70W dim	90221904

more specs on page 540

### ALWAYS USE

recessed housing + plaster kit

one lamp | 171x171x179mm

175x175 190 4-25

	CODE
	90012013
	90012021

two lamps | 327x171x179mm

331x175 190 4-25

	CODE
	90012014
	90012022

three lamps | 482x171x179mm

485x175 190 4-25

	CODE
	90012015
	90012023

four lamps | 638x171x179mm

640x175 190 4-25

	CODE
	90012016
	90012024

more information on page 549