


D43 ↓ 30.8% ↑ 69.2% Φ: 7800 lm



**Work equipment**

**Connected load**

**Power consumption**

**Luminous flux**

**Luminous efficiency**

**Light type/-color**

**Colour temperatur**

**Color rendering index**

**Light distribution**

**Chromaticity tolerance LED**

**Glare control**

**System of protection**

**Class of protection**

**Technology**

**Housing**

**Light source cover**

**Weight (net)**

**Mains lead**

**Design**

**Fastening**

**Maximum ambient temperature**

**Special features**

**Power supply unit**

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 95 W

approx. 8.890 lm

approx. 93 lm/W

adjustable white

approx. 3.000 - 6.500 K

CRI ≥ 80

Direct/indirect

< 3 SDCM

See luminaire type

IP 20

I

Switchable

Sectional aluminium; Anodised; Aluminium  
coloured anodised

Acrylic (PMMA); White opal

ca. 6,9 kg

Connector; 5 pin

mounted version

Wall bracket

25 °C

General light, indirect, 3000K-6500K, Ra≥80;  
Reading light, direct, 2700K, Ra≥90; Examination  
light; direct; 4000K; 36W; Ra≥95; R9≥50; External  
control device required for DALI Device Type 6;  
Biodynamic light VTL