823500


Product Sheet

Alfia

Square luminaire for installation in the wall - recessed. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: transparent or sandblasted, fixed to the frame through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP54 In compliance with ENGS98-1 standards Class of insulation: mains: I, LED module: II, III Installation: MiniAfIa is equipped with two cable holders for 5www.attingheweight but two cable holders for three single wires. Alfia is equipped with two cable holders for 5www.attingheweight but cable holders. Installation requires a dedicated box to be ordered seen and the sufficient or t

Alfia / Transparent Glass





Product Code Details



Light Source



HIT-CE 35W G12






ARES s.r.l - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

IP54 ♥⊕C€

Available Colors for this Version



Warnings

Wall Recessed




Protection against impact. IK 08 - 05,00 joule

Recessed wall fitting

Light Flux, Placement







Code: 60 Box for installation 250 x 250 H 110 mm