121154115

Product Sheet



THE OUTDOOR BY FLOS


ARES s.r.I - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

Andrea

Pole top luminaire for installation on pole or wall (dedicated wall mounting bracket). Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content), top cover in pre-galvanised sheet (lower side painted in white) secured to the housing by four extruded aluminium brackets. Acrylic diffuser: clear or opal, 3mm thick. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65. In compliance with EN60598-1 standards. Class of insulation: I; LED module: II. Installation: the fixture is equipped with 1000mm cable. Re-lamping through the removal of a disc fitted on the top cover. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

Andrea / Pole Ø 102mm - Transparent Acrylic Diffuser





IP65 ♥ ⊕ C€

Available Colors for this Version



6. grey



3. anthracite

Warnings

Pole Top



Pole Top Luminaire



Pre-wired with approx 1000mm of cable.



Protection against impact. IK 07 - 02,00 joule

Light Flux, Placement





Product Code Details

121154115

Light Source



HIE 100W E27





Code: 236 2 way terminal block 3 poles IP68 (Ø 5,5÷12 mm cable)

.3 anthracite



Code: 4145 In-Ground Pole (+500 mm Root) With Access Door With Terminal Block 4x1,5-16mmq ø102mm H 4000mm (+500 mm) .6 grey



Code: 4155 In-Ground Pole (+500 mm Root) With Access Door With Terminal Block 4x1,5-16mmq ø102mm H 5000mm (+500 mm) .6 grey .3 anthracite



Code: 4140
Pole with Base and Access Door
With Terminal Block 4x1,5-16mmq
ø102mm
H 4000mm
.6 grey
.3 anthracite



Code: 4150
Pole with Base and Access Door
With Terminal Block 4x1,5-16mmq
ø102mm
H 5000mm
.6 grey
.3 anthracite



Code: 116 Base plate and pole fixing bolts 230 x 230 x H 200 mm