

533012

Product Sheet

ares
THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)
www.aresill.net - flos.outdoor@flos.com

Anna

Outdoor / Indoor round luminaire for installation on ceiling or wall surface-mounted.
Configuration: opal plastic diffuser with satin finish for a high light emission uniformity ratio.
Die-cast aluminium fixing back-plate and turned aluminium structure and heat sink.
Magnetic finish frame to hide the fixing screws. The luminaire is coated with polyester powders in single or double colour. Protection rating: IP65 In compliance with EN 60598-1 standards Class of Insulation: I Installation: the luminaire is equipped with two IP65 cable holders for rubber cables 5<Ø<10mm (Anna Ø210 and Ø310) or cables 6<Ø<13mm (Anna Ø410) and a quick-connect 2-pole terminal block. Outdoor installation requires suitable flexible cables assuring the watertightness of the cable holder.

Anna310 Mid-Power LED



Product Code Details

533012

Light Source



WARM WHITE 3000K MID-POWER LEDs 14,1W/220÷240V
Total power 18W
LED lm 2049 ÷ OUTPUT lm 1200
CRI>80
Integral electronic power supply
Dimmable on request



IP65   

Available Colors for this Version



Warnings

Decorative



Ceiling fitting



Protection against impact.
IK 08 - 05,00 joule



The fitting is equipped with 2
cable input.



Wall fitting

Wall/Ceiling



Ceiling fitting



Protection against impact.
IK 08 - 05,00 joule



The fitting is equipped with 2
cable input.




Wall fitting

Light Flux, Placement



Accessories



Code: 237

SPD: (Surge Protection Device) 275Vac

Maximum discharge current 10KA (8/20 μ s)

Maximum operating current 5A

Suitable for series connection - IP66