# 533021

**Product Sheet** 




ARES s.r.l - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

### Anna

Outdoor / Indoor round luminaire for installation on ceiling or wall surface-mounted. Configuration: opal plastic diffuser with satin finish for a high light emission uniformity ratio. Die-cast aluminium fixing back-plate and turned aluminium structure and heat sink. Magnetic finish frame to hide the fixing screws. The luminaire is coated with polyester powders in single or double colour. Protection rating: IP65 In compliance with EN 60598-1 standards Class of Insulation: I Installation: the luminaire is equipped with two IP65 cable holders for rubber cables 5<Ø<10mm (Anna Ø210 and Ø310) or cables 6<Ø<13mm (Anna Ø410) and a quick-connect 2-pole terminal block. Outdoor installation requires suitable flexible cables assuring the watertightness of the cable holder.


#### Anna410 Mid-Power LED



mage not found
http://www.aresill.net/img/prod\_vers offs/ama410\_enitape/wene/8:jpg\_dr/anna4

# IP65 ♥ ⊕ C€

#### Available Colors for this Version



#### Warnings

#### Decorative



Ceiling fitting



The fitting is equipped with 2 cable input.



Wall fitting

#### **Product Code Details**

533021

Light Source



NATURAL WHITE 4000K MID-POWER LEDs 27,9W/110÷240V Total power 34W LED Im 4318 ÷ OUTPUT Im 2340 CRI>80

Integral electronic power supply Dimmable on request



## Wall/Ceiling



Ceiling fitting



Protection against impact. IK 08 - 05,00 joule

Protection against impact.

IK 08 - 05,00 joule



The fitting is equipped with 2 cable input.



Wall fitting

#### Light Flux, Placement









Code: 237 SPD: (Surge Protection Device) 275Vac Maximum discharge current 10KA (8/20µs) Maximum operating current 5A Suitable for series connection - IP66