

115147113

Product Sheet

ares
THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)
www.aresill.net - flos.outdoor@flos.com

Camilla


Rectangular luminaire for installation in the wall - recessed. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: sandblasted with silkscreen border, fixed to the aluminium structure through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65 In compliance with EN 60598-1 standards Class of insulation: mains: I; LED module: I, III; RGB: III Installation: Electrical components housed into the removable back side. Wiring through two M16 cable glands for (4,5 10mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland. Installation requires a dedicated box to be ordered separately.

IP65   CE

Available Colors for this Version



Camilla Mid-Power LED / L 230 mm - Diffused light



Warnings

Wall Recessed



Recessed wall fitting



Remote device required for 24V version



The fitting is equipped with 2 cable input.



Protection against impact. IK 08 - 05,00 joule

Light Flux, Placement



Product Code Details

115147113

Light Source



NATURAL WHITE 4000K MID-POWER LEDs 4W/100÷240V
Total power 7W
lm LED 557 ÷ lm OUTPUT 112
CRI >80
Integral electronic power supply



Accessories



Code: 123
Box for installation
255 x 110 x H 95 mm



Code: 237
SPD: (Surge Protection Device) 275Vac
Maximum discharge current 10KA (8/20µs)
Maximum operating current 5A
Suitable for series connection - IP66