

105174144

Product Sheet

ares

THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico


v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)

www.aresill.net - flos.outdoor@flos.com

Martina Aqua


Adjustable spotlight. Configuration: AISI 316L stainless steel structure and adjustable bracket. Glass diffuser: transparent or sandblasted with silkscreen border, fixed through a robotic gluing system. Protection rating: IP68 (1000mm). In compliance with EN60598-1 standards. Class of insulation: III. Installation: the luminaire is equipped with 5000mm cable. Martina Aqua 24V and Maxi Martina Aqua 24V are equipped with a dc/dc highly efficient resin-coated converter that removes electromagnetic interference and protects against polarity reversal and sudden voltage peak. Parallel wiring required. Mini Martina Aqua, Martina Aqua RGB and Maxi Martina Aqua RGB requires connection in series. SELV equivalent remote power supply required. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

Martina Aqua RGB Power LED / Inox 316L
Underwater - Transparent Glass -
Adjustable - Medium Beam 35°



IP68 (1MT)

Available Colors for this Version



Warnings

Underwater



Pre-wired with approx 5000mm of cable.



Remote electronic power supply



Protection against impact.
IK 05 - 0,70 joule MiniMartina 316L
IK 07 - 2,00 joule Martina 316L/MaxiMartina 316L

Light Flux, Placement



Product Code Details

105174144

Light Source



RGB POWER LED 3,4W/3CHx350mA

Total power 3,4W

Remote electronic power supply to be ordered



Accessories



Code: 136
Ground spike
H 200 mm



Code: 142
DMX Controller
Dimmer switch for recessed box (60 mm hole centres)



Code: 187
DMX splitter
Electronic device to regenerate the DMX signal.
1 input and 7 output. 12÷24Vdc
Power supply to be ordered (87 or 175 recommended)



Code: 141
Supported n. of lamps: 10
Power supply with DMX interface for RGB fixtures
36W/220÷240V-3CHx350mA
(3CHx10x1W) DMX control allowed
IP67 CLASS I SELV EQ.



Code: 143
DMX Controller
Stand-alone/PC interface



Code: 186
DMX cable
Shielded twisted pair with 110 Ohm constant impedance