05211145


Product Sheet

Martina Aqua

Adjustable spotlight. Configuration: AISI 316L stainless steel structure and adjustable bracket. Glass diffuser: transparent or sandblasted with silkscreen border, fixed through a robotic gluing system. Protection rating: IP68 (1000mm). In compliance with EN60598-1 standards. Class of insulation: III. Installation: the luminaire is equipped with 5000mm cable. Martina Aqua 24V and Maxi Martina Aqua 24V are equipped with a dc/dc highly edition resin-coated converter that removes electromagnetic interference and protects against polarity reversal and sudden voltage peak. Parallel wiring required. Mini Martina Aqua, Martina Aqua RGB and Maxi Martina Aqua RGB requires connection in series. SELV equivalent remote power supply required. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

MaxiMartina Aqua Power LED / Inox 316L Underwater - Transparent Glass -Adjustable - Medium Beam 30°





ARES s.r.l - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

Available Colors for this Version




0. Inox

Warnings

Underwater



Pre-wired with approx 5000mm of cable.



Protection against impact. IK 05 - 0,70 joule MiniMartina 316 IK 07 - 2,00 joule Martina

Remote electronic power supply

Light Flux, Placement



Product Code Details



Light Source



NATURAL WHITE 4000K POWER LEDs 9,9W/24Vdc Total power 14,7W LED Im 1031 ÷ OUTPUT Im 723 CRI>80 Remote electronic power supply to be ordered



Accessories

e

Code: 136 Ground spike H 200 mm



Code: 215 3/4 way terminal block 3 poles IP68 (Ø 5,5÷12 mm cable)



Code: 236 2 way terminal block 3 poles IP68 (Ø 5,5÷12 mm cable)





Code: 110 Supported n. of lamps: 6 Power supply 70W/220÷240V - 24Vdc IP67 CLASS II SELV EQ.



Code: 155 Supported n. of lamps: 3 Power supply 50W/120÷240V - 24Vdc IP67 CLASS II SELV.