

# 105256145

Product Sheet

## ares

THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico

v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)

www.aresill.net - flos.outdoor@flos.com

## Martina Aqua

Adjustable spotlight. Configuration: AISI 316L stainless steel structure and adjustable bracket. Glass diffuser: transparent or sandblasted with silkscreen border, fixed through a robotic gluing system. Protection rating: IP68 (1000mm). In compliance with EN60598-1 standards. Class of insulation: III. Installation: the luminaire is equipped with 5000mm cable. Martina Aqua 24V and Maxi Martina Aqua 24V are equipped with a dc/dc highly efficient resin-coated converter that removes electromagnetic interference and protects against polarity reversal and sudden voltage peak. Parallel wiring required. Mini Martina Aqua, Martina Aqua RGB and Maxi Martina Aqua RGB requires connection in series. SELV equivalent remote power supply required. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.


IP68 (1MT)  

### Available Colors for this Version



0. Inox

MaxiMartina Aqua RGB Power LED / Inox  
316L Underwater - Transparent Glass -  
Adjustable - Medium Beam 35°



### Warnings

#### Underwater



Pre-wired with approx  
5000mm of cable.



Remote electronic power  
supply



Protection against impact.  
IK 05 - 0,70 joule MiniMartina  
316L  
IK 07 - 2,00 joule Martina  
316L/MaxiMartina 316L

### Light Flux, Placement



### Product Code Details

# 105256145

Light Source



RGB POWER LEDs 13,6W/3CHx350mA

Total power 13,6W

Remote electronic power supply to be ordered



## Accessories

---



Code: 136  
Ground spike  
H 200 mm



Code: 142  
DMX Controller  
Dimmer switch for recessed box (60 mm hole centres)



Code: 187  
DMX splitter  
Electronic device to regenerate the DMX signal.  
1 input and 7 output. 12÷24Vdc  
Power supply to be ordered (87 or 175 recommended)



Code: 141  
Supported n. of lamps: 2  
Power supply with DMX interface for RGB fixtures  
36W/220÷240V-3CHx350mA  
(3CHx10x1W) DMX control allowed  
IP67 CLASS I SELV EQ.



Code: 143  
DMX Controller  
Stand-alone/PC interface



Code: 186  
DMX cable  
Shielded twisted pair with 110 Ohm constant impedance