

# Y Light

Design Studio & Partners

iGuzzini

September 2012

## Y Light -

---

**Product code:**

3042

---

**Technical description:**

Suspended fitting for direct/indirect emission designed for compact fluorescent lamps TC-L. Distribution of the luminous flow: 65% indirect light, 35% direct light. The optical assembly has painted extruded-aluminium side profiles, painted injection-moulded polycarbonate end caps and an internal painted sheet-steel structure. The polycarbonate diffuser screen has microprisms. In combination with a diffusing opaline polycarbonate film, it permits excellent diffusion of the direct component of the light. The fitting comes complete with transparent power supply cable and steel suspension cables (length 2 m), with millimetric adjustment system on the optical assembly. The fitting is mounted to the ceiling by means of steel plates covered by injection-moulded polycarbonate bases. The terminal blocks housed inside either base make it possible to have double operation.

---

**Installation:**

Suspended by means of steel cables. The fitting has a 2-m long electric cable.

---

**Dimension:**

D=620 x 405mm H=62mm

---

**Colour:**

Grey (15)

---


**Mounting:**

Ceiling pendant

---

**Wiring:**

Dimmable digital electronic control gear (DALI). The electronic components needed for operation are housed into the internal structure and are covered by a sheet-steel protection plate. Occupies 2 DALI addresses.



---

Complies with EN605981 and pertinent regulations

