

Y Light

Design Studio & Partners

iGuzzini

September 2012

Y Light -

Product code:

3048

Technical description:

Suspended fitting for direct/indirect emission designed for compact fluorescent lamps TC-L. Distribution of the luminous flow: 65% indirect light, 35% direct light. The optical assembly has painted extruded-aluminium side profiles, painted injection-moulded polycarbonate end caps and an internal painted sheet-steel structure. The polycarbonate diffuser screen has microprisms. In combination with a diffusing opaline polycarbonate film, it permits excellent diffusion of the direct component of the light. The fitting comes complete with transparent power supply cable and steel suspension cables (length 2 m), with millimetric adjustment system on the optical assembly. The fitting is mounted to the ceiling by means of steel plates covered by injection-moulded polycarbonate bases. The terminal blocks housed inside either base make it possible to have double operation.

Installation:

Suspended by means of steel cables. The fitting has a 2-m long electric cable.

Dimension:

D=1196 x 203m H=62mm

Colour:


Grey (15)

Mounting:

Ceiling pendant

Wiring:

Dimmable digital electronic control gear (DALI). The electronic components needed for operation are housed into the internal structure and are covered by a sheet-steel protection plate. Occupies 1 DALI address.



Complies with EN605981 and pertinent regulations

