

September 2012

## Y Light -

---

**Product code:**3049

---

**Technical description:**

Suspended fitting for direct/indirect emission designed for fluorescent lamps T16 (T5). Distribution of the luminous flow: 65% indirect light, 35% direct light. The optical assembly has painted extruded-aluminium side profiles, painted injection-moulded polycarbonate end caps and an internal painted sheet-steel structure. The polycarbonate diffuser screen has microprisms. In combination with a diffusing opaline polycarbonate film, it permits excellent diffusion of the direct component of the light. The fitting comes complete with transparent power supply cable and steel suspension cables (length 2 m), with millimetric adjustment system on the optical assembly. The fitting is mounted to the ceiling by means of steel plates covered by injection-moulded polycarbonate bases. The terminal blocks housed inside either base make it possible to have double operation.

---

**Installation:**

Suspended by means of steel cables. The fitting has a 2-m long electric cable.

---

**Dimension:**

D=1496 x 203mm H=62mm

---

**Colour:**

Grey (15)

---

**Mounting:**


Ceiling pendant

---

**Wiring:**

Electronic control gear complete with inverter and battery unit with permanent emergency light (1-hour autonomy) and terminal blocks designed for REST MODE. The electronic components needed for operation are housed inside the optical assembly.

---



Complies with EN605981 and pertinent regulations

