

September 2012

**Greenwich - Direct/indirect light pendant luminaire w/100W Ba 15d auxiliary halogen lamp 150W/150W HIT****Product code:**

3127

**Technical description:**

Indoor up-down luminaire for 2x150W HIT metal halide lamps with 1x100W Ba 15d pre-starting halogen lamp. Made up of turned aluminium body and bent extruded aluminium ring joined to the body with screws on spacers. PG11 for waterproof power supply cable. Tempered protection glasses with silicone gaskets fixed to the body with bayonet screws, aluminium component-holding plate with steel screws, power supply unit with power factor correction and anti-short circuit protection system. 99.85% superpure aluminium optics with polishing and sandblasting finish, 60°-100° adjustment device for downlight emission and anti-glare spill-ring.

**Installation:**

Suspended by means of rigid aluminium rods with +/-80 mm adjustment device, aluminium base for wall or ceiling installation and aluminium trapezoidal element for luminaire support. Suspended by means of steel cables with piston fixing system and aluminium power supply base.

**Dimension:**

H 320 mm - D 620 mm

**Colour:**

Grey (15)

**Weight [Kg]:**

20

**Mounting:**

Ceiling pendant

**Wiring:**

Wiring for 2x150W HIT discharge lamps contained inside the body of the luminaire.

Complies with EN605981 and pertinent regulations

