

# Mini Light Air

Design Bruno Gecchelin

iGuzzini

September 2012



**Mini Light Air - Dark-VDU module L1000 cd/m2 >65° up/down with electronic control gear T1628/54W**

---

**Product code:**

3187

---

**Technical description:**

Suspended lighting system designed for fluorescent light sources with up/down dark light luminous emission. The product permits down-light-only emission by means of a top cover made of plastic material. Controlled-luminance optic L 1000 cd/m2 for at > 65° suitable for use in environments with VDUs according to standard EN 12464-1. The lamellar optic with bi-parabolic profile is made of anodised specular superpure aluminium. The structure of the fitting is made of galvanised painted sheet-steel; the lamp-holding supports are made of galvanised painted sheet-steel; the end caps are made of polycarbonate. The top protection screen (to be ordered separately) is made of transparent polycarbonate subjected to anti-UV treatment. The power-supply cable is transparent and the cables are subjected to antioxidant treatment. The modules can be combined by means of direct and corner (90°) couplings.

---

**Installation:**

Suspended installation. The suspension system (to be ordered separately) has sheet-steel supporting plates with polycarbonate covering bases and steel suspension cables with a millimetric adjustment system (applied to the modules).

---

**Dimension:**

140x40 mm L = 1400 mm

---

**Colour:**

White (01)|Grey (15)

---

**Weight [Kg]:**

2,9

---

**Mounting:**

Ceiling pendant

---

**Wiring:**

The fitting is equipped with 28/54W T16 Multiwatt electronic ballast. The product is designed for through wiring by means of special terminal boards and electrical wires with 1,5 mm2 cross-section housed inside the aluminium profile. The system is designed to switch on two groups of fittings separately.

---

Complies with EN605981 and pertinent regulations

