

September 2012

**IGZMini Light Air - module with digital dimmable electronic (DALI) control gear 35 W T16 FH****Attention! Code out of production****Product code:**

3189

**Technical description:**

Suspended lighting system designed for fluorescent light sources with up/down light emission of dark-light kind. This product permits down-light-only emission by means of a top cover made of plastic material. Product complete with controlled-luminance optic  $L = 1000 \text{ cd/m}^2$  for  $\alpha > 65^\circ$  suitable to be used in environments with VDUs according to Standard EN 12464-1. The lamellar optic with bi-parabolic profile is made of anodised specular superpure aluminium. The structure of the fitting is made of galvanised painted sheet steel, the lamp-holding supports are made of galvanised painted sheet steel, and the end caps of polycarbonate. The top protection screen (to be ordered separately) is made of transparent polycarbonate subjected to anti-UV treatment. The power-supply cable is transparent and the cables are subjected to antioxidant treatment. The modules can be combined by means of direct and corner ( $90^\circ$ ) couplings.

**Installation:**

Suspended application. The suspension system (to be ordered separately) has sheet-steel supporting plates with polycarbonate covering bases and steel suspension cables with a millimetric adjustment system (applied to the modules).

**Dimension:**

140x40 mm L = 1700 mm

**Colour:**

White (01)|Grey (15)

**Mounting:**

Ceiling pendant

**Wiring:**

The fitting comes complete with a dimmable digital electronic ballast (DALI). The product is designed for through wiring by special terminal boards housed inside the modules and comes equipped with switch dim - regulation also by means of standard electric button. The system is able to switch on three groups of fittings separately. Occupies 1 DALI address.

Complies with EN605981 and pertinent regulations

