September 2012



140

Mini Light Air - General lighting module up/down with electronic control gear T1628/54W

Product code:

3194

Technical description:

Suspended lighting system designed for fluorescent light sources with up/down general light luminous emission. The product permits down-light-only emission by means of a top cover made of plastic material. The fitting is equipped with a polycarbonate microprismatic diffusing screen subjected to anti-UV treatment. The structure of the fitting is made of galvanised painted sheet-steel; the lamp-holding supports are made of galvanised painted sheet-steel; the end caps are made of polycarbonate. The top protection screen (to be ordered separately) is made of transparent polycarbonate subjected to anti-UV treatment. The power-supply cable is transparent and the cables are subjected to antioxidant treatment. The modules can be combined by means of direct and corner (90°) couplings.

Installation:

Suspended installation. The suspension system (to be ordered separately) has sheet-steel supporting plates with polycarbonate covering bases and steel suspension cables with a millimetric adjustment system (applied to the modules).

Dimension:

140x40 mm L = 1400 mm

Colour:

White (01)|Grey (15)

Weight [Kg]:

2,3

40

Mounting:

Ceiling pendant

Wiring:

The fitting is equipped with 28/54W T16 Multiwatt electronic ballast. The product is designed for through wiring by means of special terminal boards and electrical wires with 1,5 mm2 cross-section housed inside the aluminium profile. The system is designed to switch on two groups of fittings separately.









Complies with EN605981 and pertinent regulations





