

September 2012

**Mini Light Air - General lighting up/down module with electronic control gear and permanent emergency light T16 35/49/80W****Product code:**

3199

**Technical description:**

Suspended lighting system designed for fluorescent light sources with up/down general light luminous emission. The product permits down-light-only emission by means of a top cover made of plastic material. The fitting is equipped with a polycarbonate microprismatic diffusing screen subjected to anti-UV treatment. The structure of the fitting is made of galvanised painted sheet-steel; the lamp-holding supports are made of galvanised painted sheet-steel; the end caps are made of polycarbonate. The top protection screen (to be ordered separately) is made of transparent polycarbonate subjected to anti-UV treatment. The power-supply cable is transparent and the cables are subjected to antioxidant treatment. The modules can be combined by means of direct and corner (90°) couplings.

**Installation:**

Suspended installation. The suspension system (to be ordered separately) has sheet-steel supporting plates with polycarbonate covering bases and steel suspension cables with a millimetric adjustment system (applied to the modules).

**Dimension:**

140x40 mm L = 1700 mm

**Colour:**

White (01)|Grey (15)

**Weight [Kg]:**



3,8

**Mounting:**

Ceiling pendant

**Wiring:**

The fittings is equipped with T16 25/49/80W Multiwatt electronic ballast with inverter and battery pack for emergency light. The product is designed for through wiring by means of special terminal boards and electrical wires with 1,5 mm<sup>2</sup> cross-section housed inside the aluminium profile. The special terminal boards designed for REST MODE ensure permanent emergency light for 1 hour. The system is designed to switch on two groups of fittings separately.



Complies with EN605981 and pertinent regulations

