

September 2012

**Spin - Low-voltage and discharge downlighter 3x50 W QR CBC 51 + 35 W HI-PAR 20****Attention! Code out of production****Product code:**

3413

**Technical description:**

Recessed fitting designed for use with several individually adjustable light sources for the simultaneous illumination of several objects using a single lighting body. Made from sheet steel, it has four low-voltage light sources - three low-voltage lamps + one discharge lamp. After installation, the only visible element of the fitting is a simple circular ring. The system is equipped with mechanical locks for both axes of rotation to ensure stability of the angle set also after routine maintenance operations.

**Installation:**

Fitting to be recessed into false ceiling by means of steel springs adjustable through mechanical lock inside the optical assembly.

**Dimension:**

D 418 mm H 302 mm

**Colour:**

White (01)

**Mounting:**

Ceiling recessed

**Wiring:**

For low-voltage lamps connect the cables of the fitting to the terminal block of the secondary of the transformer - to be ordered separately. For the discharge lamp the electrical connection is by means of fast-fitting connectors. The electrical components required for the fitting are housed in special control gear boxes (8638) to be ordered separately.

**Notes:**

For the photometric data of the fitting, refer to the photometric characteristics of the light sources.

Complies with EN605981 and pertinent regulations

