

September 2012

Sistema Easy MH-HAL - Recessed fitting with transparent glass 70 W HIT-DE (HIGH EFFICIENCY FIXTURE)**Product code:**

3927

Technical description:

Diecast aluminium recessed fitting designed to use metal-halide lamps (HIT-DE). The diecast structure acts as a heat dissipater, consequently optimising performance levels and ensuring outputs of up to 75%. The polished superpure aluminium reflector is made up of two parts. The first part, just above the light source, acts as a flow director, while the other, fastened to the fitting by means of a system of counter springs, can be removed for quick effortless maintenance. The component box, separate from the fitting, is designed for fast-connection wiring. The fastening springs guarantee excellent anchoring to false ceilings ranging from 1 to 25 mm in thickness. The fitting is designed for installation in public environments and can be positioned on surfaces made with inflammable materials.

Installation:

Recessed with 212-mm diameter holes.

Dimension:

D= 232 mm h= 115 mm

Colour:

White/Aluminium (39)|Grey/Aluminium (78)

Weight [Kg]:

0,9

Mounting:


Ceiling recessed

Wiring:

Three wiring systems: phased electromagnetic, phased electromagnetic with impulse-controlled ignitor and electronic - inside special boxes (to be ordered separately).

Notes:

With high-efficiency reflector



Complies with EN605981 and pertinent regulations

