

September 2012

**Sistema Easy MH-HAL - Recessed fitting with U.V. filter 150 W HIT-DE****Attention! Code out of production - 2012****Product code:**

3940

**Technical description:**

Diecast aluminium recessed fitting designed to use metal-halide lamps (HIT-DE). The diecast structure acts as a heat dissipater, consequently optimising performance levels and ensuring outputs of up to 75%. The polished superpure aluminium reflector is made up of two parts. The first part, just above the light source, acts as a flow director, while the other, fastened to the fitting by means of a system of counter springs, can be removed for quick effortless maintenance. The component box, separate from the fitting, is designed for fast-connection wiring. The fastening springs guarantee excellent anchoring to false ceilings ranging from 1 to 25 mm in thickness. The fitting is designed for installation in public environments and can be positioned on surfaces made with inflammable materials.

**Installation:**

Recessed with 212x212 mm holes.

**Dimension:**

232x232 mm h= 115 mm

**Colour:**


White/Aluminium (39)|Grey/Aluminium (78)

**Mounting:**

Ceiling recessed

**Wiring:**

Three wiring systems: phased electromagnetic, phased electromagnetic with impulse-controlled ignitor and electronic - inside special boxes (to be ordered separately).



232



212x212

Complies with EN605981 and pertinent regulations

