

September 2012

## Sivra compact - Flat-screen small module with automatic adjustment system and dimmable digital electronic control gear 7x24 W T16

**Product code:**

3945

**Technical description:**

Fluorescent lighting system with a sheet-steel body comprising the lamps (supplied standard) and dimmable digital electronic ballasts, a sheet-steel reflector and an aluminium frame supporting the thermoplastic material diffusing screen. The fitting uses 7 fluorescent lamps T16 24W with different colour temperatures (four 6500 K lamps and three 2700 K lamps). In order to access the ballast and lamp compartment and maintain the illuminating body, lower the frame supporting the screen by specific springs.

**Installation:**

Recessed in all kinds of 1 to 40 mm thick false ceilings with 600x600 grids and fixed by means of steel plates.

**Dimension:**

596x596mm h=180mm

**Colour:**

White (01)

**Weight [Kg]:**

10

**Mounting:**

Ceiling recessed

**Wiring:**

Wiring for lamp power supply composed of 4 dimmable digital electronic ballasts and fast-coupling terminal blocks inside the product. Occupies 4 DALI adress.

**Notes:**

The luminous intensity and the colour temperature can be controlled through the Light Equalizer Central (code 9833) and the Controller (code 9842).

Complies with EN605981 and pertinent regulations

