


September 2012

**Optica - Recessed luminaire with digital dimmable electronic (DALI) control gear 2x32W TC-TEL****Attention! Code out of production****Product code:**

4294

**Technical description:**

Downlight designed for use with a 2x32W compact fluorescent lamp in the horizontal position. Thanks to its professional optics the luminance of the reflector can be limited to values smaller than 200 cd/sqm with angles of observation greater than 60° with respect to the vertical axis (ref. CIBSE LG3 and DIN 5035 Teil 7 A60). Two brackets made of galvanized sheet steel are fixed to the die-cast aluminium perimetric ring to support the component box, also made from sheet steel. The lamp holder is fixed to the component box, which can be extracted from the fitting for easier maintenance. The superpure aluminium reflector is screwed to the fitting at the bottom.

**Installation:**

Holes of 280 mm diameter for recessed installation. The brackets for fastening the support ring can be adjusted through sliders to fit false ceilings 1 to 30 mm thick.

**Dimension:**

461x289mm H 195mm

**Colour:**

White/Aluminium (39)

**Mounting:**

Ceiling recessed

**Wiring:**

Digital dimmable electronic (DALI) ballast designed for two 32W compact fluorescent lamps. Occupies 1 DALI address.

**Notes:**

Dimmable ballast available upon request.

Complies with EN605981 and pertinent regulations

