


Last information update: June 2018

**Surface-mounted luminaire - Neutral white - integrated control gear - diffused light****Product code**

5030

**Technical description**

Diffused light ceiling- / wall-mounted luminaire. LED lamps. Fixing plate made of shaped sheet steel which is painted white. Aluminium LED support acts as a heat sink. Opal PMMA diffuser screen - the shape and finish give uniform, comfortable light emission. Neutral white high efficiency LED

**Installation**

Ceiling- or wall-mounted. Plate is fixed to surface using screws and screw anchors (not supplied). LED unit removable using turn & lock system. Thermoplastic screen manually fixed on plate with rotation springs.

**Dimension (mm)**

Ø426x125

**Colour**

White (01)

**Weight (Kg)**

2.11

**Mounting**

wall surface|ceiling surface

**Wiring**

quick-coupling terminal block on fixing plate; set up for pass-through wiring between two or more luminaires; quick-connector links control gear box and removable LED unit.

Complies with EN60598-1 and pertinent regulations



IP40

**Product configuration: 5030****Product characteristics**

Total lighting output [Lm]: 1976  
Total power [W]: 18.2  
Luminous efficacy [Lm/W]: 108.6  
Life Time: > 50,000h - L80 - B10 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 211  
Emergency luminous flux [Lm]: /  
Voltage [V]: -  
Number of optical assemblies: 1

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 76  
Lamp code: LED  
ZVEI Code: LED  
Nominal power [W]: 17  
Nominal luminous [Lm]: 2600  
Lamp maximum intensity [cd]: /  
Beam angle [°]: /

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: 1.2  
Colour temperature [K]: 4000  
CRI: 80  
Wavelength [Nm]: /  
MacAdam Step: 3

# Polar



# Isolux

