


Last information update: June 2018

**Surface-mounted luminaire - Warm white - integrated control gear - diffused light****Product code**

5031

Technical description

Diffused light ceiling- / wall-mounted luminaire. LED lamps. Fixing plate made of shaped sheet steel which is painted white. Aluminium LED support acts as a heat sink. Opal PMMA diffuser screen - the shape and finish give uniform, comfortable light emission. Warm white high efficiency LED

Installation

Ceiling- or wall-mounted. Plate is fixed to surface using screws and screw anchors (not supplied). LED unit removable using turn & lock system. Thermoplastic screen manually fixed on plate with rotation springs.

Dimension (mm)

Ø426x125

Colour

White (01)

Weight (Kg)

2.11

Mounting

wall surface|ceiling surface

Wiring

quick-coupling terminal block on fixing plate; set up for pass-through wiring between two or more luminaires; quick-connector links control gear box and removable LED unit.

Complies with EN60598-1 and pertinent regulations



IP40

**Product configuration: 5031****Product characteristics**

Total lighting output [Lm]: 1976
Total power [W]: 18.2
Luminous efficacy [Lm/W]: 108.6
Life Time: > 50,000h - L80 - B10 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 211
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 76
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 17
Nominal luminous [Lm]: 2600
Lamp maximum intensity [cd]: /
Beam angle [°]: /

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 1.2
Colour temperature [K]: 3000
CRI: 80
Wavelength [Nm]: /
MacAdam Step: 3

Polar



Isolux

