

Last information update: June 2018

**70W HIT(BLV)****Product code**

5688

Technical description

Outdoor wall luminaire made of aluminium. A protection glass located in the lower section of the fitting creates an 88° light cone directed downwards. The control gear is contained in a die cast aluminium box used for wall fixing. The box has a hole protected with plastic material for the wiring. The body of the fitting is fixed to the plate with a screw, allowing for easy lamp replacement.

Installation

Fixed to the wall with fischer screws.

Dimension (mm)

280x150x165

Colour

Grey (15)

Weight (Kg)

4.89

Mounting

wall surface

Wiring

Wiring for discharge lamps contained in the box.

Complies with EN60598-1 and pertinent regulations



960°C

IP44

**Product configuration: 5688+L070**

L070: Metal halide lamp 70W G12 3000 K (BLV)

Product characteristics

Total lighting output [Lm]: 636

Total power [W]: 83

Luminous efficacy [Lm/W]: 7.7

Ambient temperature range: from -20°C to +35°C.

Total luminous flux at or above an angle of 90° [Lm]: 0

Emergency luminous flux [Lm]: /

Voltage [V]: 230

Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 11

Lamp code: L070

ZVEI Code: HIT

Nominal power [W]: 70

Nominal luminous [Lm]: 6000

Lamp maximum intensity [cd]: /

Beam angle [°]: 66° / 60°

Number of lamps for optical assembly: 1

Socket: G12

Ballast losses [W]: 13


Colour temperature [K]: 3000

CRI: 85

Wavelength [Nm]: /

MacAdam Step: /

Polar



Isolux

