

Last information update: June 2018

**70W HIT(BLV)****Product code**

5688

**Technical description**

Outdoor wall luminaire made of aluminium. A protection glass located in the lower section of the fitting creates an 88° light cone directed downwards. The control gear is contained in a die cast aluminium box used for wall fixing. The box has a hole protected with plastic material for the wiring. The body of the fitting is fixed to the plate with a screw, allowing for easy lamp replacement.

**Installation**

Fixed to the wall with fischer screws.

**Dimension (mm)**

280x150x165

**Colour**

Grey (15)

**Weight (Kg)**

4.89

**Mounting**

wall surface

**Wiring**

Wiring for discharge lamps contained in the box.

Complies with EN60598-1 and pertinent regulations



960°C

IP44



CE



EAC

**Product configuration: 5688+L071**

L071: Metal halide lamp 70W G12 4200 K (BLV)

**Product characteristics**

Total lighting output [Lm]: 594

Total power [W]: 83

Luminous efficacy [Lm/W]: 7.2

Ambient temperature range: from -20°C to +35°C.

Total luminous flux at or above an angle of 90° [Lm]: 0

Emergency luminous flux [Lm]: /

Voltage [V]: 230

Number of optical assemblies: 1

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 11

Lamp code: L071

ZVEI Code: HIT

Nominal power [W]: 70

Nominal luminous [Lm]: 5600

Lamp maximum intensity [cd]: /

Beam angle [°]: 66° / 60°

Number of lamps for optical assembly: 1

Socket: G12

Ballast losses [W]: 13


Colour temperature [K]: 4200

CRI: 85

Wavelength [Nm]: /

MacAdam Step: /

Polar



Isolux

