

September 2012

## Lineup - Biodynamic light module

Attention! Code out of production - 2012

### Product code:

5812

### Technical description:

Biodynamic lighting fitting recessed into the false ceiling for fluorescent light sources with asymmetric light emission of wall-washer kind. The structure and removable end caps are made of painted galvanised sheet steel, the lamp cover of painted aluminium, and the reflector of superpure aluminium. The installation brackets are made of galvanised sheet steel. The fitting is treated with RAL9016 liquid painting. The lamp cover has a fall-prevention system made up of a double steel safety cable. The modules can be combined to make continuous lines.

### Installation:

Installation is carried out either by special brackets or on the surface of a modular false ceiling. No tools are needed to tighten the brackets, which are suitable for false ceilings 1 to 35 mm thick. The hole for the recessed product is 168x1187 mm.

### Dimension:

180x1198

### Colour:

White (01)

### Weight [Kg]:

4,4

### Mounting:


Ceiling recessed

### Wiring:

The fitting is complete with two dimmable digital electronic ballasts (DALI). The fast-coupling terminal boards for electrical connection can be accessed both from the back of and from inside the product. The product is designed for through wiring and comes equipped with switch dim - regulation also by means of standard electronic button. The connection to the control system Light Equalizer is completely Plug&Play. Occupies 2 DALI addresses.

### Notes:

The module comes complete with light sources. The electronic control unit and the relevant panel needed for operation must be ordered separately.



Complies with EN605981 and pertinent regulations

