

September 2012

## Compact Easy - Large module with flat screen and electronic control gear, multi-watt ballasts, and separate switches 4x28/54 W T16

**Product code:**  
6205

**Technical description:**

Modular system for use with fluorescent lamps. Recessed installation into false ceilings (IP40) and walls (IP53). The product has: white painted steel sheet body and reflector and an aluminium frame that supports the thermoplastic diffusing screen. Screen has a flat surface. Fitting uses 4 T16 28/54 W lamps and 28/54 W electronic multiwatt ballasts. The terminal boxes are predisposed for separate switches of the two groups of lamps. The screen-frame aluminium group is connected to the body of the fitting with special springs. These springs have a system that prevents the screen-frame group from falling, remaining attached to the body of the product on one side, therefore making maintenance operations quite easy. Electrical connection via terminal box, housed inside the product's body, requires no tools.

**Installation:**

Installation into all types of 600x1200 mm false ceilings with cross-sections between 1 and 40 mm. The hooking and fastening system is performed via steel plate brackets.

**Dimension:**

596x1196mm

**Colour:**

White (01)

**Weight [Kg]:**



16

**Mounting:**

Ceiling recessed

**Wiring:**

Fitting has electronic multiwatt ballasts. Terminal box predisposed for separate switches of the two lamp groups.



Complies with EN605981 and pertinent regulations

