

September 2012

Compact Easy - Large module with flat screen and RGB dynamic colour change 6x28 W + 2x54 W T16

Product code:

6224

Technical description:

Modular system for use with fluorescent lamps. Recessed installation into false ceilings (IP40) and walls (IP53). The product has: white painted steel sheet body and reflector and an aluminium frame that supports the thermoplastic diffusing screen.

Screen has a flat surface. The screen-frame aluminium group is connected to the body of the fitting with special springs.

These springs have a system that prevents the screen-frame group from falling, remaining attached to the body of the product on one side, therefore making maintenance operations quite easy. Electrical connection via terminal box, housed inside the product's body, requires no tools. Product is equipped with 2xRED, 2xGREEN, 2xBLUE, 2xWHITE 3000K lamps. Dimmable electronic DALI ballasts are pre-configured and allow for connection to the COLOUR EQUALIZER control system without any programming.

The product is compatible with DALI control systems.

Installation:

Installation into all types of 600x1200 mm false ceilings with cross-sections between 1 and 40 mm. The hooking and fastening system is performed via steel plate brackets.

Dimension:

596x1196mm

Colour:

White (01)

Weight [Kg]:

21

Mounting:



Ceiling recessed

Wiring:

Control gear has 4 electronic dimmable DALI ballasts pre-configured for plug&play connection (with no need for programming) to COLOUR EQUALIZER system. Occupies 4 DALI addresses.

Notes:

Occupies 4 DALI addresses.



Complies with EN605981 and pertinent regulations

