

September 2012

Express - with electronic control gear and dimmer 75/100W 12V QT 12 - Flood**Product code:**

6371

Technical description:

Adjustable projector, with adaptor for installation on mains voltage tracks, and front ring both made of thermoplastic material.

Shells and rods made of die-cast aluminium. Optical compartment and power supply inside one single body with two different colour finishes: grey/black or white/black. 100WQT12 low voltage halogen lamp with flood optic and dimmable electronic transformer.

The projector's optic has a lamp focus manual device located behind the optical compartment. 360° rotation around the vertical axis and 0°/90° inclination in relation to the horizontal plane. Fitting has special mechanical blocking mechanisms for both rotations, for precision aim. The same tool is used for the blocking mechanisms by turning two screws: one in front of the rod and the other on the track adapter. An accessory-holder ring can hold up to three flat accessories at once. One external accessory can be also applied: either an asymmetric screen, directional flaps, or an anti-glare screen. All accessories can be rotated up to 360° with respect to the longitudinal axis of the projector. Flood optic reflector made of mirrored ultrapure aluminium. Changing the reflector requires no tools.

Installation:

Electrified track ceiling/wall installation via special base that can be ordered separately.

Dimension:

L 153 mm - D 110 mm - H 172 mm

Colour:

Black/White (47)|Grey/Black (74)

Weight [Kg]:


1,7

Mounting:

Three circuit track

Wiring:

Dimmable electronic components for low voltage halogen lamps contained inside the special box that is equipped with the fitting.



Complies with EN605981 and pertinent regulations

