

September 2012

**Express - with electronic control gear 150W HIT - Flood****Product code:**

6381

**Technical description:**

Adjustable projector, with adaptor for installation on mains voltage tracks, and front ring both made of thermoplastic material. Shells and rods made of die-cast aluminium. Optical compartment and power supply inside one single body with two different colour finishes: grey/black or white/black. Flood optic 150W HIT discharge lamp with electronic power supply group. The projector's optic has a lamp focus manual device located behind the optical compartment. 360° rotation around the vertical axis and di 0°/90° inclination in relation to the horizontal plane. Fitting has special mechanical blocking mechanisms for both rotations, for precision aim. The same tool is used for the blocking mechanisms by turning two screws: one in front of the rod and the other on the track adapter. An accessory-holder ring can hold one flat accessory. One external accessory can also be applied: either an asymmetric screen, directional flaps, or an anti-glare screen. All accessories can be rotated up to 360° with respect to the longitudinal axis of the projector. Flood optic reflector made of mirrored ultrapure aluminium. Changing the reflector requires no tools.

**Installation:**

Electrified track ceiling/wall installation via special base that can be ordered separately.

**Dimension:**

L 189 mm - D 141 mm - H 203 mm

**Colour:**

Black/White (47)|Grey/Black (74)

**Weight [Kg]:**

2,8

**Mounting:**

Three circuit track

**Wiring:**

Dimmable electronic components for discharge lamps contained inside the special box that is equipped with the fitting.

Complies with EN605981 and pertinent regulations

