

September 2012

**Lux - with electronic control gear 70W HIT (CDM-R 111)****Product code:**

6415

**Technical description:**

Adjustable projector with adaptor for installation on mains voltage tracks and front ring both made of thermoplastic material. Optical compartment and component box made of die-cast aluminium. 70W CDM R111 discharge lamp complete with electronic power supply group. 360° rotation around the vertical axis; 360° rotation of the optical assembly via a continuous friction joint. For both rotations the projector has special mechanical blocking mechanisms for precision aim. The same tool is used for the blocking mechanisms by turning two screws: one on the track adapter and one on the component box next to the joint. Front ring installed via bayonet system, in order to hold the safety glass. An accessory-holder ring can hold a variety of accessories and up to three flat accessories at once. One external accessory can be also applied: either an asymmetric screen, directional flaps, or an anti-glare screen. All accessories can be rotated up to 360° with respect to the longitudinal axis of the optical compartment. IP40 for optical assembly with optional glass diffusers.

**Installation:**

Electrified track or ceiling/wall installation via special base that can be ordered separately.

**Dimension:**

L 343 mm - D 135 mm - H 231 mm

**Colour:**

White (01)|Grey/Black (74)

**Weight [Kg]:**

1,7

**Mounting:**

Ceiling surface|Three circuit track

**Wiring:**

Dimmable electronic components for discharge lamps contained inside the special box that is equipped with the fitting.

Complies with EN605981 and pertinent regulations

