

September 2012

Lux - with electronic control gear 70W HIT - Flood**Product code:**

6419

Technical description:

Adjustable projector with adaptor for installation on mains voltage tracks and front ring both made of thermoplastic material.

Optical compartment and component box made of die-cast aluminium. Ultrapure mirrored aluminium reflector with special faceting

that improves the light beam distribution. Can be substituted without the use of tools. Flood optic, with 70W HIT discharge

lamp complete with electronic power supply group. 360° rotation around the vertical axis; 360° rotation of the optical assembly

via a continuous friction joint. For both rotations the projector has special mechanical blocking mechanisms for precision

aim. The same tool is used for the blocking mechanisms by turning two screws: one on the track adapter and one on the component

box next to the joint. Front ring installed via bayonet system, in order to hold the safety glass. An accessory-holder ring

can hold a variety of accessories and up to three flat accessories at once. One external accessory can be also applied: either

an asymmetric screen, directional flaps, or an anti-glare screen. All accessories can be rotated up to 360° with respect

to the longitudinal axis of the optical compartment. IP40 for optical assembly.

Installation:

Electrified track or ceiling/wall installation via special base that can be ordered separately.

Dimension:

L 343 mm - D 135 mm - H 231 mm

Colour:

White (01)|Grey/Black (74)

Weight [Kg]:


1,8

Mounting:

Ceiling surface|Three circuit track

Wiring:

Dimmable electronic components for discharge lamps contained inside the special box that is equipped with the fitting.



Complies with EN605981 and pertinent regulations

