

September 2012

Express - with electronic transformer DALI 75/100W 12V QT 12 - Spot**Product code:**

6431

Technical description:

Adjustable spotlight with adapter for installation on DALI mains voltage tracks. Optical assembly and control gear contained in single body available in two finishes (grey/black or white/black). Die-cast aluminium shells and brackets; adapter and front ring made of thermoplastic material. Closing element of the two shells made of sheet steel. Equipped with Q12 100W low voltage halogen lamp with spot optic complete with DALI electronic transformer. Superpure specular aluminium reflector for spot optic that can be changed without tools. The spotlight optic is provided with lamp focusing by means of manual device on the back of the optical assembly. The fitting can rotate around the vertical axis by 360° with 0/90° inclination with respect to horizontal plane. It is provided with mechanical locks for aiming in both rotations, which are applied by acting with the same tool on two screws, one in front of the rod and one on the track adapter. The spotlight is provided with an accessory-holding ring that can contain up to three flat accessories at the same time. One more external component can be applied, chosen from asymmetrical screen, adjustable flaps and anti-glare screen. All the external accessories can be rotated by 360° with respect to the longitudinal axis of the projector.

Installation:

In DALI electrified track, wall/ceiling mounted or with special base to be ordered separately.

Dimension:

L 153 mm - D 110 mm - H 172 mm

Colour:

Black/White (47)|Grey/Black (74)

Weight [Kg]:



1,7

Mounting:

Ceiling surface|Dali track

Wiring:

DALI electronic components for low voltage halogen lamp contained in box integrated into the fitting.



Complies with EN605981 and pertinent regulations

