

September 2012

Express - with electronic transformer DALI 100W 12V QR 111**Product code:**

6433

Technical description:

Adjustable spotlight with adapter for installation on DALI mains voltage tracks. Optical assembly and control gear contained in single body with two finishes (grey/black or white/black). Die-cast aluminium shells and brackets; adapter and front ring made of thermoplastic material. Closing element of the two shells made of sheet steel. Equipped with QR 111 100W low voltage halogen lamp complete with DALI electronic transformer. The fitting can rotate around the vertical axis by 360° with 0/90° inclination with respect to horizontal plane. It is provided with mechanical locks for aiming in both rotations, which are applied by acting with the same tool on two screws, one in front of the rod and one on the track adapter. The spotlight is provided with an accessory-holding ring that can contain up to three flat accessories at the same time (75W max. wattage). One more external component can be applied, chosen from asymmetrical screen, adjustable flaps and anti-glare screen. All the external accessories can be rotated by 360° with respect to the longitudinal axis of the projector.

Installation:

In DALI electrified track, wall/ceiling mounted or with special base to be ordered separately.

Dimension:

L 189 mm - D 141 mm - H 203 mm

Colour:

Black/White (47)|Grey/Black (74)

Weight [Kg]:

2,5

Mounting:



Dali track

Wiring:

DALI electronic components for low voltage halogen lamp contained in box integrated into the fitting.

Notes:

The DALI spotlights are provided with special adapter and are only compatible with iGuzzini DALI tracks.



Complies with EN605981 and pertinent regulations

