

September 2012

Lux - with electronic transformer DALI 75/100W 12V QT 12 - Flood**Product code:**

6461

Technical description:

Adjustable spotlight with adapter for installation on DALI mains voltage track. Adapter and front ring made of thermoplastic material, optical assembly and component-holding box made of die-cast aluminium. Superpure specular aluminium reflector with special faceted finish that improves the distribution of the luminous beam and possibility to change it without tools. Flood optic, with QT 12 100W low voltage halogen lamp complete with DALI electronic transformer. 360° rotation of the body around the vertical axis and of the optical assembly by means of continuous-friction articulation. For both rotations the spotlight is provided with mechanical locks for aiming that are applied by acting with the same tool on two screws, one on the DALI track adapter and one on the component-holding box near the articulation. Multiple accessories are available for installation with accessory-holding ring, which can contain up to three flat elements at a time. One more external component can be applied, chosen from asymmetrical screen, adjustable flaps and anti-glare screen. All external accessories can be rotated by 360° with respect to the longitudinal axis of the optical assembly.

Installation:

In DALI electrified track or wall/ceiling mounted with special base to be ordered separately.

Dimension:

L 277 mm - D 106 mm - H 194 mm

Colour:

White (01)|Grey/Black (74)

Weight [Kg]:

1,25

Mounting:

Ceiling surface|Dali track

Wiring:

DALI electronic components for low voltage halogen lamp contained in box integrated into the fitting.

Notes:

The DALI spotlights are provided with special adapter and are only compatible with iGuzzini DALI tracks.

Complies with EN605981 and pertinent regulations

