iGuzzini

September 2012

639

Design Jean Michel Wilmotte



6469

Technical description:

Express - DALI LED neutral white 8x1W - Medium

Adjustable spotlight with adapter for installation on DALI mains voltage track for 8x1W high-performing LED with monochromatic Neutral White (4200K) emission. Optic with plastic lenses, medium beam (25°) and protection glass with serigraphy. Complete with lamp and DALI electronic ballast. The optical assembly and control gear are contained in the same body. The shells and brackets are made of die-cast aluminium, the adapter and the front ring are made of thermoplastic material, the closing element of the two shells is made of sheet steel. The fitting can rotate around the vertical axis by 360° with 0/90° inclination with respect to horizontal plane. It is provided with mechanical locks for aiming in both rotations, which are applied by acting with the same tool on two screws, one in front of the rod and one on the track adapter. The spotlight is provided with accessory-holding ring for one flat accessory. One more external component can be applied, chosen from asymmetrical screen, adjustable flaps and anti-glare screen. All the external accessories can be rotated by 360° with respect to the longitudinal axis of the projector.

Installation:

In DALI electrified track or wall/ceiling mounted with special base to be ordered separately.

Dimension:

L 153 mm - D 110 mm - H 172 mm

Colour:

Black/White (47)|Grey/Black (74)

Weight [Kg]:

2

Mounting: Ceiling surface|Dali track

Wiring:

The DALI electronic components for LEDS are contained inside the fitting.

Notes:

The DALI spotlights are provided with special adapter and are only compatible with iGuzzini DALI tracks.



Complies with EN605981 and pertinent regulations