Sydecar

iGuzzini

September 2012




Sydecar - with dimmable electronic transformer 50W 12V QT 12 - Flood

Product code:

Technical description:

Spotlight made of die-cast aluminium and thermoplastic material, with adapter for installation on electrified track. Spotlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. The luminaire has mechanical locks for aiming, operated using the same tool on two screws, one at the side of the power supply box shell and one on the track adapter. Spotlight equipped with accessory holding ring designed to contain one flat accessory. Another external component can also be applied, selected from an asymmetrical screen, directional flaps and an anti-glare screen. The luminaire with 50W 12V QT2 flood optic comes complete with a dimmable electronic transformer. IP 40 on the optical assembly with the use of accessory glass components.



Installation:

Dimension:

on an electrified track or using a suitable power supply unit

	Tr
4	6

113

L 113 mm – D 78 mm – H 139 mm Colour:

White (01)|Grey/Black (74)

Weight [Kg]:

0,7

Mounting: Dali track

Wiring:

Dimmable electronic components for LV halogen lamp housed in the box with which the luminaire is equipped

Notes:

A maximum of 1 flat accessory can be fitted



Complies with EN605981 and pertinent regulations