

September 2012

IGZAction|IGZAction incasso|IGZAction incasso luce generale - Dark-VDU module 65° with digital dimmable electronic (DALI) control gear 2x28 W T16 (T5)
Attention! Code out of production

Product code:
6604

Technical description:

Suspended, ceiling-mounted or recessed lighting system designed for fluorescent light sources with up/down light emission. This product permits down-light-only emission by means of a top cover (to be ordered separately) made of plastic material. It has a controlled-luminance optic for 65° suitable to be used in environments with VDUs according to Standard EN 12464-1. The lamellar optic with bi-parabolic profile and its external surface are made of anodised specular superpure aluminium and are equipped with a fall-prevention system. The structure of the fitting is made of painted extruded aluminium; the lamp-holding supports are made of galvanised painted sheet steel; and the end caps (to be ordered separately) of polycarbonate. The top protection screen (to be ordered separately) is made of transparent polycarbonate subjected to anti-UV treatment. The power-supply cable is transparent and the cables are subjected to antioxidant treatment. The modules can be combined by means of direct and corner 90° couplings as well as structural modules (to be ordered separately).

Installation:

The suspension system (to be ordered separately) has sheet-steel supporting plates with polycarbonate covering bases and steel suspension cables with a millimetric adjustment system (applied to the modules). Ceiling application by means of an aluminium structure (to be ordered separately). Recessed and semi-recessed installation by means of a structure designed for application to false ceilings 12.5mm and 15mm thick, with concealed rim (to be ordered separately).

Dimension:

130x65mm L 1177mm

Colour:

White (01)|Grey (15)

Mounting:

Ceiling pendant

Wiring:

Dimmable digital electronic control gear (DALI) with switch-dim (adjustment also by means of a standard electronic button). It is designed for through wiring by means of special terminal boards housed inside the aluminium profile. The system is able to switch on three groups of fittings separately. It takes up 1 DALI address.

Notes:

Accessories available: top closing cover, end caps, various installation and combination accessories.

Complies with EN605981 and pertinent regulations

