

September 2012

Action - Dark-VDU module L1000 cd/m² >65° with dimmable electronic DALI control gear T162x35/49W**Product code:**

6605

Technical description:

Suspended, surface-mounted or recessed lighting system designed for fluorescent light sources with up/down light emission. The product permits downlight-only emission by means of a top cover (to be ordered separately) made of plastic material. The modules are complete with terminal boards and cables for through wiring. Ready for switch-on of 3 groups of fittings. The product has a controlled-luminance optic for 65° suitable to be used in environments with VDUs according to Standard EN 12464-1. The lamellar optic with bi-parabolic profile and its external surface are made of anodised specular superpure aluminium and are equipped with fall-prevention system. The specular optics can be removed without tools for ordinary maintenance operations. The structure of the fitting is made of painted extruded aluminium; the lamp-holding supports are made of galvanised painted sheet steel; and the end caps (to be ordered separately) of polycarbonate. The top protection screen (to be ordered separately) is made of transparent polycarbonate subjected to anti-UV treatment. The power-supply cable is transparent and the cables are subjected to antioxidant treatment. The modules can be combined by means of direct and corner 90° couplings as well as structural modules (to be ordered separately). The suspension system (to be ordered separately) has sheet-steel supporting plates with polycarbonate covering bases and steel suspension cables with a millimetric adjustment system (applied to the modules). Ceiling application by means of an aluminium structure (to be ordered separately). Recessed and semi-recessed installation system by means of a structure designed for application to false ceilings 12.5mm and 15mm thick, with concealed rim (to be ordered separately).

Installation:

Suspended, surface-mounted, semi-recessed or recessed installation.

Dimension:

130x65mm L 1477mm

Colour:

White (01)|Grey (15)

Mounting:

Ceiling pendant|Ceiling recessed|Ceiling surface

Wiring:

The fitting comes complete with DALI dimmable electronic ballast and is designed for switch-dim, with regulation also with standard electronic button. It is designed for through wiring by means of special terminal boards housed inside the aluminium profile. The system is able to switch on three groups of fittings separately. It takes up 1 DALI address.

Complies with EN605981 and pertinent regulations

