
IGZAction|IGZAction incasso|IGZAction incasso luce generale

Design Jean Michel Wilmotte

iGuzzini

September 2012



IGZAction|IGZAction incasso|IGZAction incasso luce generale - General lighting module up/down with electronic control gear 2x54 W T16 (T5)

Attention! Code out of production

Product code:

6610

Technical description:

Suspended, ceiling-mounted or recessed lighting system designed for fluorescent light sources with up/down light emission. This product permits down-light-only emission by means of a top cover (to be ordered separately) made of plastic material. The product produces general light and has an extruded polycarbonate screen with diffusing opal surface subjected to anti-UV treatment. The structure of the fitting is made of painted extruded aluminium; the lamp-holding supports are made of galvanised painted sheet steel; and the end caps (to be ordered separately) of polycarbonate. The top protection screen (to be ordered separately) is made of transparent polycarbonate subjected to anti-UV treatment. The power-supply cable is transparent and the cables are subjected to antioxidant treatment. The modules can be combined by means of direct and corner 90° couplings as well as structural modules (to be ordered separately).

Installation:

The suspension system (to be ordered separately) has sheet-steel supporting plates with polycarbonate covering bases and steel suspension cables with a millimetric adjustment system (applied to the modules). Ceiling application by means of an aluminium structure (to be ordered separately). Recessed and semi-recessed installation by means of a structure designed for application to false ceilings 12.5mm and 15mm thick, with concealed rim (to be ordered separately).

Dimension:

130x65mm L 1177mm

Colour:

White (01)|Grey (15)

Mounting:

Ceiling pendant

Wiring

The fitting comes complete with an electronic ballast. It is designed for through wiring by means of special terminal boards housed inside the aluminium profile. The system is able to switch on three groups of fittings separately.

Notes:

Accessories available: top closing cover, end caps, various installation and combination accessories.

Complies with EN605981 and pertinent regulations







