

September 2012

Action - Module wall-washer with electronic control gear T16 28/54W**Product code:**

6616

Technical description:

Suspended, ceiling-mounted or recessed lighting system designed for fluorescent light sources with wall-washer light emission. The wall-washer optic is made up of a superpure aluminium reflector and a painted extruded aluminium lamp cover. The structure of the fitting is made of painted extruded aluminium; the lamp-holding supports are made of galvanised painted sheet steel; and the end caps (to be ordered separately) of polycarbonate. The power-supply cable is transparent and the cables are subjected to antioxidant treatment. The modules can be combined by means of direct and corner 90° couplings as well as structural modules (to be ordered separately). Ideal distance from the wall: 100cm.

Installation:

The suspension system (to be ordered separately) has sheet-steel supporting plates with polycarbonate covering bases and steel suspension cables with a millimetric adjustment system (applied to the modules). Ceiling application by means of an aluminium structure (to be ordered separately). Recessed and semi-recessed installation by means of a structure designed for application to false ceilings 12.5mm and 15mm thick, with concealed rim (to be ordered separately).

Dimension:

130x65mm L 1177mm

Colour:

White (01)|Grey (15)

Mounting:



Ceiling pendant|Ceiling recessed|Ceiling surface

Wiring:

The fitting comes complete with an electronic ballast. It is designed for through wiring by means of special terminal boards housed inside the aluminium profile. The system is able to switch on three groups of fittings separately.

Notes:

Accessories available: end caps, various installation and combination accessories.



Complies with EN605981 and pertinent regulations

