

September 2012

Action - Module 1 compartment complete with electronic components L=400 HIT 20W flood**Product code:**

6620

Technical description:

Suspended, ceiling-mounted or recessed lighting system with one optical assembly designed for metal-halide sources with flood optic. The structure of the fitting is made of painted extruded aluminium; the lamp-holding supports are made of galvanised painted sheet steel; and the end caps (to be ordered separately) of polycarbonate. The power-supply cable is transparent and the cables are subjected to antioxidant treatment. The modules can be combined by means of direct and corner 90° couplings as well as structural modules (to be ordered separately). The lamps are located in a die-cast aluminium housing with a superpure-aluminium optic that can be adjusted 355° with respect to the vertical axis and up to 65° with respect to the horizontal axis

Installation:

The suspension system (to be ordered separately) has sheet-steel supporting plates with polycarbonate covering bases and steel suspension cables with a millimetric adjustment system (applied to the modules). Ceiling application by means of an aluminium structure (to be ordered separately). Recessed and semi-recessed installation by means of a structure designed for application to false ceilings 12.5mm and 15mm thick, with concealed rim (to be ordered separately).

Dimension:

L 400mm h 66mm

Colour:


White (01)|Grey (15)

Wiring:

The fitting comes complete with an electronic ballast. It is designed for through wiring by means of special terminal boards housed inside the aluminium profile. The system is able to switch on three groups of fittings separately.

Notes:

Accessories available: end caps, spill ring, various installation and combination accessories.



Complies with EN605981 and pertinent regulations

