



September 2012

**OFX - Single module with electronic control gear (DALI) - 3 x 54W****Product code:**

6635

**Technical description:**

Pendant fitting, for use with T16 lamps. Up/down light emission. Single Module. Body made of one profile of extruded painted aluminium. Zinc-coated and painted steel sheet lamp holders. Polycarbonate end caps. Upper safety screen (to be ordered separately) made of transparent polycarbonate with anti-UV treatment. Down-light optics made of ultrapure anodized mirrored aluminium with bi-parabolic profiles. Controlled luminance:  $L=1000 \text{ cd/m}^2$  for  $\alpha>65^\circ$ , in compliance with the EN 12464-1 norm. The optical group has a safety cable that saves it from falling. Up-light emission via ultrapure aluminium reflector.

Separate switches for up-light and down-light emission. Dimmable DALI electronic ballasts. Product is equipped with installation system. Transparent power cable, electric cables with anti-oxidation surface treatment.

**Installation:**

Suspension installation via steel plates covered by injection-moulded polycarbonate bases. Equipped with transparent power cable and suspension cables with precision adjustment system, positioned on the optical assembly.

**Dimension:**

180 x 40 mm - L = 1188 mm

**Colour:**

White (01)|Grey (15)

**Mounting:**

Ceiling pendant

**Wiring:**

Fitting equipped with dimmable digital DALI electronic power supply - Switch dim function. Can be controlled via a normal electric button.

**Notes:**

Occupies 2 DALI addresses.

Complies with EN605981 and pertinent regulations

