

September 2012

Rib - Large body luminaire complete with protection screen - 250W HIT**Product code:**

6760

Technical description:

Direct light pendant luminaire, designed to use HIT 250W metal halide lamp. Component-holding box consists of two die-cast aluminium half shells with captive fixing screws. Die-cast aluminium inner lamp holder container. Bent sheet steel inner plate for holding components and lamp holder fastening elements. The electric components in the box can be inspected and maintained even after product installation. Die-cast aluminium suspension cable coupling element and steel safety cable clamp for power cable. Spin-formed aluminium reflector with high efficiency low-glossy surface finish. Connections protected by special seals which guarantee the degree of protection. Die-cast aluminium lower ring with sodium – calcium safety glass applied using silicone, seal and anti-fall safety cable. Ring insertion and removal system with fast-lock fastening levers and safety screws. Accessory kit for pendant luminaire with die-cast aluminium base for anchoring to the ceiling, complete with power cable, quick coupling and steel suspension cable millimetric adjustment device.

Installation:

Pendant with accessory kit (code 6856). Cable length available 2.0 m.

Dimension:

Ø 511 mm - H 735 mm

Colour:

Grey/Aluminium (78)

Mounting:

Ceiling pendant

Wiring:

Electromagnetic ballast and components for discharge lamp integrated in luminaire. Terminal board for connection to mains with quick coupling (pendant kit code 6856); connection between mains power and control gear using fast-lock coupling system.

Complies with EN605981 and pertinent regulations

