

September 2012

Sistema 44 - Faceted reflector with electronic control gear 2x13W TC-DEL**Product code:**

8162

Technical description:

Downlight designed for use with 2x13W compact fluorescent lamps TC-DEL. The polycarbonate optical assembly complies with the CENELEC HD 444.2.1 specifications (suitable for installation in public places, since it does not create any combustion). The polycarbonate control gear box is fixed to the optical assembly and forms a single body with it. ABS metallized low-luminance reflector, methacrylate protective screen located between the reflector and the optical assembly. The light flow recuperator in superpure aluminium in the upper part of the optical assembly comes standard with the fitting. Patented fixing system for false ceilings with adjustable steel springs with mechanical stop in the optical assembly. Control gear box made of extruded aluminium and connected to the fitting.

Installation:

Fixed to false ceilings with adjustable steel springs with mechanical stop. Hole diameter on the false ceiling 209 mm

Dimension:

D 220mm H 145mm

Colour:

White/Aluminium (39)

Weight [Kg]:

1,5

Mounting:

Ceiling recessed

Wiring:

Control gear contained in the control gear box and composed of Quicktronic electronic ballast. Control gear box dimensions: 174x110 mm h 61 mm.

Notes:

Available accessories decorative glass (8749) and glass decorative cylinder (8746).

Complies with EN605981 and pertinent regulations

