Light Up Walk professional

Design Jean Michel Wilmotte **iGuzzini**

September 2012



Light Up Walk professional - Fluorescent projector 26/32/42 W TC-TEL - wall-washer optic (antislip glass)
Attention! Code out of production

Product code:
B233

Technical description:
Luminaire recessed into the ground with die-cast aluminium body and outer casing; stainless-steel frame and screws; anodised polished superpure aluminium reflector. It is designed to use compact fluorescent lamps with wall-washer optic. The outer casing for installation can be ordered separately from the optical assembly. Visual comfort is guaranteed by the a black steel antiglare screen. The optical assembly is closed at the top by a hardened sodium-lime glass (thickness 19 mm) with silicone gasket compressed by an AISI 304 stainless-steel frame. The lower section houses a decompression box for cascade wiring by 6-pole terminal block and double stainless-steel cable-clamp M24x1.5. This section is connected to the optical assembly through a nickel-plated brass cable clamp M15x1. This makes it easier to open the upper glass by eliminating negative pressure inside the optical assembly and the pump effect on the supply cable. The body-optical assembly is equipped with a locking system with two stainless-steel captive screws on which two extruded aluminium supports can slide. The locking system ensures positioning and anchoring of the optical assembly to the outer casing. The acrylic painting of the body-optical assembly and outer casing guarantees protection against UV rays and the external environment. The coupling of frame, glass, optical assembly and outer casing guarantees resistance to a static load of 5000 kg. Glass surface temperature does not exceed 50°C.

Installation:
Recessed into the ground by means of an outer casing. The upper rim of the installed outer casing should protrude out of the pavement by 1mm MAX. The outer casing has an upper diameter of 385 mm, a lower diameter of 495 mm, and is 126 mm high.

Dimension:
D=410mm H=124mm

Colour:
Steel (13)

Mounting:
Ground recessed

Wiring:
Control gear inside the body of the fitting.

Notes:
Available accessories: outer casing, coloured filters, suction cup and end cap for the outer casing.

Complies with EN605981 and pertinent regulations

IP67 IK10